LGME

PRODUCT NAME: LIQUID ARGON



## 1. Chemical Product and Company Identification

Linde Gas Middle East LLC, 22nd Floor, Nation Towers, Corniche Road, P. O Box 109155, Abu Dhabi, United Arab Emirates. Direct Line: +971.2.6140200, Fax Line: +971.2.6140219, Website: www.linde-gas.ae

#### PRODUCT NAME:

ARGON, REFRIGERATED LIQUID

CHEMICAL NAME: Argon

COMMON NAMES/SYNONYMS: Argon, liquid

### 2. Composition, Information on Ingredients

Ingredient	% Volume	TLV-ACGIH <sup>2</sup>
Argon	99.985% min.	Simple
Formula: <b>Ar</b>		Asphyxiant

#### 3. Hazards Identification

#### EMERGENCY OVERVIEW

Simple Asphyxiant - This product does not contain oxygen and may cause asphyxia if released in a confined area. Maintain oxygen levels above 19.5%. Contact with product may cause frostbite or freeze burns in exposed tissues. Nonflammable.

#### **ROUTE OF ENTRY:**

Skin Contact	Skin Absorption	Eye Contact	Inhalation	Ingestion
Yes	No	Yes	Yes	No

#### HEALTH EFFECTS:

Exposure Limits:	No
Irritant:	No
Sensitization:	No
Teratogen:	No
Reproductive Hazard:	No
Mutagen:	No
Synergistic Effects:	None reported

#### **EYE EFFECTS:**

Contact with product may cause tissue freezing.

#### **SKIN EFFECTS:**

Contact with product may cause tissue freezing.

# PRODUCT NAME: LIQUID ARGON



### **INGESTION EFFECTS:**

Ingestion is unlikely. Contact with product may cause tissue freezing.

### **INHALATION EFFECTS:**

Product is a non-toxic simple Asphyxiant. Effects of oxygen deficiency resulting from simple Asphyxiant may include: rapid breathing, diminished mental alertness, impaired muscular coordination, faulty judgment, depression of all sensations, emotional instability, and fatigue. As asphyxiation progresses, nausea, vomiting, prostration and loss of consciousness may result, eventually leading to convulsions, coma, and death. Oxygen deficiency during pregnancy has produced developmental abnormalities in humans and experimental animals.

### 4. First Aid Measures

### EYES:

Never introduce ointment or oil into the eyes without medical advice! In case of freezing or cryogenic "burns" caused by rapidly evaporating liquid. DO NOT WASH THE EYES WITH HOT OR EVEN TEPID WATER! Remove victim from the source of contamination. Open eyelids wide to allow liquid to evaporate. If pain is present, refer the victim to an ophthalmologist for treatment and follow up. If the victim cannot tolerate light, protect the eyes with a light bandage.

#### SKIN:

For dermal contact or frostbite: Remove contaminated clothing and flush affected areas with lukewarm water. DO NOT USE HOT WATER. A physician should see the patient promptly if the cryogenic "burn" has resulted in blistering of the dermal surface or deep tissue freezing.

### **INGESTION:**

A physician should see the patient promptly if the cryogenic "burn" has resulted in blistering of the dermal surface or deep tissue freezing.

### **INHALATION:**

PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF OVEREXPOSURE. RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS. Victims should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. Unconscious persons should be moved to an uncontaminated area, and if breathing has stopped, administer artificial resuscitation and supplemental oxygen. Further treatment should be symptomatic and supportive.

#### 5. Fire Fighting Measures

Conditions of Flammability	Flash Point	Method
Not flammable	None	Not applicable
Auto-ignition Temperature	LEL %	UEL %
None	None	None
Hazardous combustion products	Sensitivity to mechanical shock	Sensitivity to static discharge
None	None	None

#### FIRE AND EXPLOSION HAZARDS:

None. Nonflammable.

#### **EXTINGUISHING MEDIA:**

None required. Use as appropriate for surrounding materials.

#### 6. Accidental Release Measures

be certain to purge piping with inert gas prior to attempting repairs. If leak is in container or container valve, contact the appropriate person in Linde Gas Middle East LLC.

## PRODUCT NAME: LIQUID ARGON



### 7. Handling and Storage

### Use only in well-

Must ALWAYS be kept upright. Specialized trucks are needed for their movement. Do not drag, slide or roll

Vessels-

If there is a malfunction or other type of operations problem with the vessel, contact the closest SIGAS location immediately for assistance.

#### Vacuum-

Due to the extremely cold liquid, uninsulated transfer lines may condense air. The liquefied air may flash of nitrogen, leaving oxygen enriched liquid. Do not allow the liquefied air to contact oils, greases, or other combustible materials such as asphalt and motor oil.

Vessels for liquid argon are designed specifically for argon service. Vessels and associated structures are not designed to support higher density fluids. Density, liquid at saturation pressure at 2.17 o K (-271 o C) : 0.146 Kg/l.

Never carry a compressed gas cylinder or a container of a gas in cryogenic liquid form in an enclosed space such as a car trunk, van or station wagon. A leak can result in a fire, explosion, asphyxiation or a toxic exposure.

#### 8. Exposure Controls, Personal Protection

### **EXPOSURE LIMITS<sup>1</sup>**:

Ingredient	% Volume	TLV-ACGIH <sup>2</sup>
Argon	99.985%	Simple
Formula: <b>Ar</b>		Asphyxiant

#### **ENGINEERING CONTROLS:**

Local exhaust to prevent accumulation of high concentrations so as to reduce the oxygen level in the air to less than 19.5%.

#### **EYE/FACE PROTECTION:**

Safety goggles or glasses as appropriate for the job. Face shield recommended when handling cryogenic liquid material.

#### **SKIN PROTECTION:**

Protective gloves of material appropriate for the job. Insulated gloves recommended when handling cryogenic liquid material.

#### **RESPIRATORY PROTECTION:**


Positive pressure air line with full-face mask and escape bottle or self-contained breathing apparatus should be available for emergency use.

#### **OTHER/GENERAL PROTECTION:**

Safety shoes or other footwear as appropriate for the job.

#### LGME

# PRODUCT NAME: LIQUID ARGON



PARAMETER	VALUE	UNITS
Physical state (gas, liquid, solid)	: Liquid.	
Vapor pressure	: Above cr	itical temp.
Vapor density $(Air = 1)$	: 1.38	
Evaporation point	: Not Avai	lable
Boiling point	: -302.6	
	: -185.9	
Freezing point	: -308.9	
	: -189.4	
рН	: Not Appli	cable
Specific gravity	: Not Avai	lable
Oil/water partition coefficient	: Not Avai	lable
Solubility (H20)	: Very slig	ht
Odor threshold	: Not Appli	cable
Odor and appearance	: Colorless	, odorless gas

#### **10.** Stability and Reactivity

### **STABILITY:**

Stable

#### **INCOMPATIBLE MATERIALS:** None

#### **HAZARDOUS POLYMERIZATION:**

Does not occur.

#### 11. Disposal Considerations

Do not attempt to dispose of residual waste or unused quantities. Return in the shipping container PROPERLY LABELED, WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP IN PLACE to Linde Gas Middle East LLC or authorized distributor for proper disposal.

#### **12.** Transport Information

Parameter	United States DOT	Canada TDG
Proper Shipping Name	Argon, refrigerated liquid	Argon, refrigerated liquid
Hazard Class	2.2	2.2
Identification Number	UN 1951	UN 1951
Shipping Label	Non Flammable Gas	Non Flammable Gas

#### 13. Hazard Classes

Sudden Release of Pressure Hazard

#### 14. Other Information

Compressed gas cylinders shall not be refilled without the express written permission of the owner. Shipment of a compressed gas cylinder which has not been filled by the owner or with his/her (written) consent is a violation of transportation regulations.



LGME

## PRODUCT NAME: LIQUID ARGON



### DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein and assume Consequences of its use: Each individual should make a determination as to the suitability of the information for their particular purpose(s).